

CLEANET PRO LITE

Shower toilet, with hidden connections! WC pan rimless, floorstanding 617890 000 S00 2



TECHNICAL DATA

Order no.	617890 000 S00 2	Power supply & consumption	Rated voltage 220-240V, 50/60Hz Power consumption in use max. 1650W Power saving mode Power cord length 1m
Certified to	SIT: CE, IPX4, EN1717 WC: EN 997 / EN 33	Weight	32,8 kg
Specifications	SIT: Duroplast, with hidden connections, with antibacterial treatment, with lowering system Lid with quick release function for cleaning Electric Bidet easy to lift for cleaning iOS and android app. connection WC: Floorstanding WC pan rimless, back to wall, washdown for min. 4,5/3-l-flush, Laufen Pro, order no. 821962 000 S00 1	Accessories incl.	SIT: Flexible hose Splash protection Y-fitting connector User manual
WC outlet	horizontal vertical 70 and 110 mm	Mounting acc. incl.	SIT: Mounting instruction Installation template, order no. WK2ES42004002 Mounting set incl. fastening kit, order no. 89389.3 WC: Fixing set, order no. 89175.7
Water inlet	G 3/8" (male)	Mounting acc. excl.	SIT: Fastening kit Direct electrical connector, order no. 89F892 Electro cable with EU-plug (type F), order no. 89E890 Electro cable with CH-plug (type J), order no. 89E891 Remote control, order no. 89G896 WC: for horizontal outlet use standard variable connection for outlet vertical 70 mm LAUFEN-connection set, order no. 89009.2 for outlet vertical 110 mm LAUFEN-connection set, order no. 89902.7
Working pressure	0.1 to 0.7 Mpa (1-7 bar)	Colours	000 – White
Working temperature	+5 to +35 °C		
Cleaning functions	Rear shower and lady shower 5 levels pressure adjustment 5 levels nozzle position adjustment 5 levels temperature adjustment Oscillating and pulsating cleaning mode		
Comfort	Night light (bowl and ambience) Remote operation possible 5 user profiles Integrated descaling function		
Hygiene	Self cleaning of shower head before and after every use Exchangeable shower nozzle tip UV nozzle disinfection		

CLEANET PRO LITE

**Shower toilet,
with hidden connections!
WC pan rimless, floorstanding
617890 000 S00 2**



TECHNICAL DRAWINGS / S 1 : 20

