

# CLEANET PRO LITE

## Shower toilet, with hidden connections! WC rimless Comfort, wall-hung 614890 000 S00 2



### TECHNICAL DATA

Order no.	614890 000 S00 2	Power supply & consumption	Rated voltage 220-240V, 50/60Hz Power consumption in use max. 1650W Power saving mode Power cord length 1m
Certified to	SIT: CE, IPX4, EN1717 WC: EN 997 / EN 33	Weight	35,8 kg
Specifications	SIT: Duroplast, with hidden connections, with antibacterial treatment, with lowering system Lid with quick release function for cleaning Electric Bidet easy to lift for cleaning iOS and android app. connection WC: Wallhung WC rimless Comfort, washdown for 4,5/3-l-flush, Laufen Pro, order no. 821962 000 S00 1	Accessories incl.	SIT: Flexible hose Splash protection Y-fitting connector User manual
WC outlet	horizontal	Mounting acc. incl.	SIT: Mounting instruction Installation template, order no. WK2ES42004002 Mounting set incl. fastening kit, order no. 89389.3 WC: Laufen EasyFit 2.0 system M12, order no. 89382.7 Water inlet pipe, order no. 89325.7
Water inlet	G 3/8" (male)	Mounting acc. excl.	SIT: Fastening kit Direct electrical connector, order no. 89F892 Electro cable with EU-plug (type F), order no. 89E890 Electro cable with CH-plug (type J), order no. 89E891 Remote control, order no. 89G896 WC: Antinoise set, order no. 89269.7 Stone screw fastening kit M12
Working pressure	0.1 to 0.7 Mpa (1-7 bar)	Colours	000 – White
Working temperature	+5 to +35 °C		
Cleaning functions	Rear shower and lady shower 5 levels pressure adjustment 5 levels nozzle position adjustment 5 levels temperature adjustment Oscillating and pulsating cleaning mode		
Comfort	Night light (bowl and ambience) Remote operation possible 5 user profiles Integrated descaling function		
Hygiene	Self cleaning of shower head before and after every use Exchangeable shower nozzle tip UV nozzle disinfection		

### TECHNICAL DRAWINGS / S 1 : 20

