SET KARTELL BY LAUFEN

Washbasin undersurface ground 81633.6



| TECHNICAL DATA | |
|-----------------------|--|
| Order no. | 81633.6 |
| Certified to | EN 31 |
| Dimensions | 800 x 460 mm |
| Basin capacity | 10.5 litre (up to bottom line of the overflow) |
| Specification | Always to be fixed to the wall. |
| | Charge 104 – 1 centre tap hole |
| Special specification | Charge 108 – 3 tap holes |
| | Charge 109 – without tap holes |
| | Charge 136 - 3 tap holes, distance 8 inches |
| | Charge 142 - without tap hole, without overflow |
| | and without open drain |
| | Charge 156 - 1 centre tap hole, without overflow |
| | and without open drain |
| Weight | 19,9 kg |
| Mounting acc. incl. | Template, order no. 89633.6 |

| Mounting acc. excl. | Mounting set M10 x 140 mm, |
|-------------------------|--|
| | order no. 89988.2 |
| Colours | see colour table |
| SPECIFICATION TEX | Т |
| Washbasin undersurfa | ace ground KARTELL BY LAUFEN, SaphirKeramik |
| EN 31, dimensions 80 | 00 x 460 mm, square |
| 1 centre tap hole, with | noverflow |
| Special feature: overfl | ow channel glazed |
| Further options / acces | ssories: Surface refinement LCC (only white), |
| 3 tap holes, without to | ap holes, 3 tap holes distance 8 inches, without |
| tap holes/overflow an | d open drain, 1 tap hole/without overflow and |
| | |

open drain, bathtubs, shower trays, furniture, accessories

Order no. 81633.6

TECHNICAL DRAWINGS / S 1 : 20

