



EAN: 4057304019340
static.hansa.com/92012219

Electra 92 series is giving you a whole new modern design with its rounded square body and spout. Giving you new fresh and updated design.

Design compliments the new trends of the modern bathroom with its more squared design.

Key Features

- Aerator with Tilt function +/- 10° for more flexible installation
- Newest Sensor technology for better detection and operation comfort
- Bluetooth technology for easy adjustment to personalize settings
- Battery and power cable

- Waschtisch
- öffentliche & halböffentliche Bereiche, Housing
- Berührungslos, Batteriebetrieb, separater Transformator, Bluetooth® fähig, Bleifrei
- Standmontage
- Chrom
- Feststehender Auslauf
- PCA® konstante Durchflussleistung unabhängig vom Fließdruck, Schwenkbar
- Rückflussverhinderer, Schmutzfilter
- Weiterentwickelter PSD-Sensor mit Autofocus, Signalleuchten, Batterie-Leer-Anzeige
- Anschluss über flexible Druckschläuche, 1 Zuleitung, für Kalt- oder Mischwasser
- HANSA 3S-Installation: System für sichere und schnelle Montage

Technische Daten

Durchflusseigenschaften

Durchfluss bei 3 bar (mit Durchflussregler)5.9 l/min

Technische Eigenschaften

Warmwasserversorgungmax. +70°C

Arbeitsdruck1-10 bar

AnschlussgrößeG3/8

Ausladung117 mm

Sicherungseinrichtung (EN1717)EB

WerkstoffVerbundwerkstoff

Software-Einstellungen

Nachlaufzeit3 s (1-20 s)

Hygienespülungoff (off/1-120 h)

Dauer Hygienespülung30 s (1-1800 s)

Max. Fließdauer2 min (1 - 1800 s)

Elektronische Eigenschaften

Elektrischer Anschluss9 V

BatterieAA 1.5 V Lithium x 2

Bluetooth version5.x (D060576)

Vorschriften

EU DirectiveC € Radio Equipment Directive 2014/53/EU , Low Voltage Directive 2014/35/EU , EMC Directive 2014/30/EU , RoHS Directive 2011/65/EU

EN StandardEN 15091, ETSI EN 301 489-1 V1.9.2 , ETSI EN 300 328 v2.2.2 , EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011+AC:2012 , EN 60335-1:2012+A11+A13+A1+A14+A2+A15:2021, Part 19.11.4

GeräuschklasseI (ISO 3822)

SchutzklasseIP 55



