

INEO INSTALLATION SYSTEM

Installation element for urinal with integrated control and for waterless urinal **INEOLINK H940102**



TECHNICAL DATA

Order no.	H940102	Installation depth	75-205 mm, wall bracket adjustable from 135-205 mm without tools
matching for	Urinal with integrated control, with Bluetooth module ANTERO, order no. H8411.0, H841152 CAPRINO PLUS, order no. H842065, H842066 LEMA, order no. H841190, H841192 TAMARO-VS NEW, order no. H841124, H841125 VAL order no. H840284, H840286 Urinal with integrated control TAMARO-S90, order no. H840103, H840104 Waterless urinal LEMA order no. H843197	Weight	8,5 kg
		Mounting acc. incl.	Urinal inlet connection, fastening material, 2x M8 threaded rods and drain elbow bracket. Outlet pipe DN 50 with urinal siphon.
		Mounting acc. excl.	Sound insulation set, order no. VS16032 C00 000 0
		Mounting information	Please note the necessary wall thickness of 80 mm in case of pre-wall installation.
		Otherwise	Compatible with U-profiles UW 50, UW 75 and the Duofix*-System (*are registered third party trademarks)
Specifications	Self-supporting steel frame for covering with plasterboard, installation onto a solid wall, in drywall constructions. Construction height 1120 mm. Non-slip leg supports, rotatable foot plates, height-adjustable 0-200 mm. Capable to resist 150 kg	Colours	Surface powder coated

TECHNICAL DRAWINGS / S 1 : 20

